

Environmental product declaration in accordance with ISO 14025, ISO 21930 and EN 15804

Owner of the declaration:	Varier Furniture AS
Program operator:	The Norwegian EPD Foundation
Publisher:	The Norwegian EPD Foundation
Declaration number:	NEPD-4462-3647-EN
Registration number:	NEPD-4462-3647-EN
ECO Platform reference number:	
Issue date:	30.12.2022
Valid to:	30.12.2027

Social[®] Turn

Varier Furniture AS

www.epd-norge.no



Varier.



Product:	Owner of the declaration:				
Social® Turn	Varier Furniture AS Contact person: Michal Klecz Phone: +47 70 24 43 50 e-mail: info@varierfurniture.com				
Program operator:	Manufacturer:				
The Norwegian EPD Foundation Pb. 5250 Majorstuen, 0303 Oslo Phone: +47 23 08 80 00 e-mail: post@epd-norge.no	Varier Furniture AS				
Declaration number:	Place of production:				
NEPD-4462-3647-EN	Varier Furniture AS Drammensveien 130 0277 Oslo Norway				
ECO Platform reference number:	Management system:				
This declaration is based on Product Category Rules:	Organisation no:				
CEN Standard EN 15804:2012+A1:2013 serves as core PCR NPCR 026:2018 Part B for furniture	NO 989 804 804				
Statement of liability:	Issue date: 30.12.2022				
The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.	Valid to: 30.12.2027				
Declared unit:	Year of study:				
1 kg Social® Turn	2022				
Declared unit with option:	Comparability:				
A1,A2,A3,A4	EPDs from programmes other than the Norwegian EPD Foundation may not be comparable				
Functional unit:	Development and verification of EPD:				
	The declaration has been developed and verified using EPD tool lca.tools ver EPD2020.11, developed by LCA.no AS. The EPD tool is integrated into the company's environmental management system, and has been				
Calculation for the chair packed in a double box					
Calculation for the chair packed in a double box General information on verification of EPD from EPD tools:	the company's environmental management system, and has been approved by EPD-Norway				
General information on verification of EPD from EPD tools: Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Individual					
General information on verification of EPD from EPD tools:	approved by EPD-Norway Developer of EPD:				

Verification of EPD tool:

Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPDNorway's procedures and guidelines for verification and approval of EPD tools.

Erik Svanes, Norsus AS

(no signature required)

Key environmental indicators	Unit	Cradle to gate A1 - A3
Global warming	kg CO2 eqv	33,07
Total energy use	MJ	474,57
Amount of recycled materials	%	58,14

Approved:

Sign

Hakon augu

Product

Market:

Global, mainly Europe.

Product description:

Social[®] is a dynamic dining chair that brings fresh life to the table by allowing you to move intuitively in every setting. Whereas the common dining chair has just one purpose and one correct sitting position, Social[®] is fundamentally different. By supporting and encouraging physical movement it enables you to make more of every moment, whatever is on the table.

Designed in collaboration between Varier Furniture and Snøhetta Architects, Social® combines Nordic simplicity and design aesthetics with innovative mobility features never seen in a dining chair. Social® is made of fiber glass-reinforced injection-molded polypropylene.

The shell contains 75% recycled polypropylene and 10% glass fiber.

The base contains 55% recycled polypropylene and 30% glass fiber.

Social $\ensuremath{^{\textcircled{\sc sc}}}$ comes in two distinct base variants: Social $\ensuremath{^{\textcircled{\sc sc}}}$ Tilt and Social $\ensuremath{^{\textcircled{\sc sc}}}$ Turn.

Product specification

Design by Snøhetta. More information on Social® here: www.varierfurniture.com/collection

Technical data:

Chair Measurement: Height: 80 cm Width: 55,7 cm Depth: 52,8 cm Seat height: 46,5 cm Weight: 8,5 kg

Box Measurement: H: 68,7cm L: 57cm W: 55,5cm

Reference service life, product

Longevity is incorporated into Varier's core values. Upholstery and cushions can be replaced over time and Varier products can be passed on to the next generation. Varier offers an extended warranty of 7 years on wooden parts and 5 years on mechanisms. Lifetime is usually longer than 15 years.

Reference service life, building

Materials	kg	%	Recycled share in material (kg)	Recycled share in material (%)	
Metal - Steel	1,71	20,29	0,00	0,00	
Plastic - Polypropylene (PP)	6,70	79,59	4,50	67,09	
Plastic - Polyethylene (LDPE)	0,01	0,12	0,00	0,00	
Total:	8,42		4,50		
Packaging	kg		Recycled share in material (kg)	Recycled share in material (%)	
Packaging - Cardboard	0,64		0,49	76,30	
Packaging - Cardboard	0,70		0,53	76,30	
Packaging - Cardboard	1,25		0,95	76,30	
Packaging - Plastic	0,02		0,00	0,00	
Packaging - Plastic	0,04		0,00	0,00	
Packaging - Plastic	0,07		0,00	0,00	
Total including packaging	11,12		6,47		

LCA: Calculation rules

Declared unit:

1 kg Social® Turn

Cut-off criteria:

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

Data quality:


Specific data for the product composition are provided by the manufacturer. They represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on registered EPDs according to EN 15804, Ostfold Research databases, ecoinvent and other LCA databases. The data quality of the raw materials in A1 is presented in the table below.

Materials	Source	Data quality	Year
Plastic - Polyethylene (LDPE)	ecoinvent 3.4	Database	2013
Metal - Steel	ecoinvent 3.4	Database	2017
Metal coating - Powder coating on steel	ecoinvent 3.4	Database	2017
Packaging - Cardboard	ecoinvent 3.4	Database	2017
Packaging - Plastic	ecoinvent 3.4	Database	2017
Plastic - Polypropylene (PP)	ecoinvent 3.6	Database	2019
Process	ecoinvent 3.6	Database	2019

Allocation:

The allocation is made in accordance with the provisions of EN 15804. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

System boundary:



Additional technical information:

LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

Transport from production place to user (A4)

Туре	Capacity utilisation (incl. return) %	Type of vehicle	Distance km	Fuel/Energy consumption	Unit	Value (l/t)
Truck	38,8 %	Truck, 16-32 tonnes, EURO 6	1260	0,043626	l/tkm	54,97
Railway					l/tkm	
Boat					l/tkm	
Other Transportation					l/tkm	

Assembly (A5)		Use (B1)			
•	Unit	Value	•	Unit	Value
Auxiliary	kg				
Water consumption	m ³				
Electricity consumption	kWh				
Other energy carriers	MJ				
Material loss	kg				
Output materials fr ste treatment	kg				
Dust in the air	kg				
VOC emissions	kg				
Maintenance (B2)/Repair (B3)			Replacement (B4)/Refurbishment (B5)		

Maintenance (B2)/Repair (B3)

	Unit	Value	•	Unit	Value
Maintenance cycle*	UCC.		Replacement cycle*		
Auxiliary	Char.		Electricity consumption	kWh	
Other resources	4/10		Replacement of worn parts		
Water consumption	m ³	A6 "	Replacement cycle* Electricity consumption Replacement of worn parts * Described above if relevant		
Electricity consumption	kWh		r a		
Other energy carriers	MJ		47.		
Material loss	kg		· Ad		
VOC emissions	kg		" are		
Operational energy (B6) and water consu	mption (B7)		End of Life (C1, Chot incl.		
	Unit	Value	· · · · · · · · · · · · · · · · · · ·	Unit	Value
	2				

	Unit	Value	· ///	Unit	Value
Water consumption	m ³		Hazardous waste disposed	kg	
Electricity consumption	kWh		Collected as mixed construction we.	kg	
Other energy carriers	MJ		Reuse	kg	
Power output of equipment	KW		Recycling		
			Energy recovery		
			To landfill	kg	

Transport to waste processing (C2)

Туре	Capacity utilisation (incl. return) %	Type of vehicle	Distance km	Fuel/Energy consumption	Unit	Value (I/t)
Truck					l/tkm	
Railway					l/tkm	
Boat					l/tkm	
Other Transportation					l/tkm	

LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

	Product stage		instal	Construction installation stage		User stage End of life stage						User stage			Beyond the system bondaries		
Raw	materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De- construction demolition	Transport	W aste processing	Disposal	Reuse-Recovery- Recycling- potential
A	41	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	. D
	Х	Х	Х	Х	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	. MND

Environmental impact

Parameter	Unit	A1	A2	A3	A4
GWP	kg CO ₂ -eq	2,66E+01	1,80E+00	4,65E+00	1,69E+00
ODP	kg CFC11 -eq	2,57E-06	3,38E-07	6,83E-08	3,18E-07
POCP	kg C ₂ H ₄ -eq	7,79E-03	2,72E-04	1,07E-03	2,56E-04
AP	kg SO ₂ -eq	1,03E-01	4,23E-03	2,82E-02	3,97E-03
EP	kg PO4 ³⁻ -eq	1,73E-02	5,55E-04	3,17E-03	5,21E-04
ADPM	kg Sb -eq	3,22E-04	5,58E-06	6,16E-08	5,25E-06
ADPE	MJ	4,11E+02	2,72E+01	4,70E+01	2,55E+01

GWP Global warming potential; ODP Depletion potential of the stratospheric ozone layer; POCP Formation potential of tropospheric photochemical oxidants; AP Acidification potential of land and water; EP Eutrophication potential; ADPM Abiotic depletion potential for non fossil resources; ADPE Abiotic depletion potential for fossil resources

Reading example: 9,0 E-03 = 9,0*10-3 = 0,009 *INA Indicator Not Assessed

Remarks to environmental impacts

Estimation data

Resource use

Parameter	Unit	A1	A2	A3	A4
RPEE	MJ	6,90E+01	4,01E-01	6,50E+00	3,77E-01
RPEM	MJ	1,50E+01	0,00E+00	0,00E+00	0,00E+00
TPE	MJ	8,40E+01	4,01E-01	6,50E+00	3,77E-01
NRPE	MJ	3,22E+02	2,78E+01	4,90E+01	2,61E+01
NRPM	MJ	1,85E+02	0,00E+00	0,00E+00	0,00E+00
TRPE	MJ	5,03E+02	2,78E+01	4,90E+01	2,61E+01
SM	kg	6,47E+00	0,00E+00	0,00E+00	0,00E+00
RSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00
NRSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00
W	m ³	3,44E-01	5,26E-03	1,73E-02	4,94E-03

RPEE Renewable primary energy resources used as energy carrier; RPEM Renewable primary energy resources used as raw materials; TPE Total use of renewable primary energy resources; NRPE Non renewable primary energy resources used as energy carrier; NRPM Non renewable primary energy resources used as materials; TRPE Total use of non renewable primary energy resources; SM Use of secondary materials; RSF Use of renewable secondary fuels; NRSF Use of non renewable secondary fuels; W Use of net fresh water

Reading example: 9,0 E-03 = 9,0*10-3 = 0,009 *INA Indicator Not Assessed

End of life - Waste

Parameter	Unit	A1	A2	A3	A4	
HW	kg	1,75E-01	1,64E-05	1,07E-05	1,54E-05	
NHW	kg	1,06E+01	1,49E+00	1,79E+00	1,40E+00	
RW	kg	INA*	INA*	INA*	INA*	
HW Hazardous waste disposed; NHW Non hazardous waste disposed; RW Radioactive waste disposed						
Reading example: 9,0 E-03 = 9,0*10-3 = 0,009 *INA Indicator Not Assessed						

End of life - Output flow

Parameter	Unit	A1	A2	A3	A4
CR	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00
MR	kg	0,00E+00	0,00E+00	5,50E-01	0,00E+00
MER	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00
EEE	MJ	INA*	INA*	INA*	INA*
ETE	MJ	INA*	INA*	INA*	INA*
CR Components for reuse; MR Materials for recycling; MER Materials for energy recovery; EEE Exported electric energy; ETE Exported thermal energy					

Reading example: 9,0 E-03 = 9,0*10-3 = 0,009 *INA Indicator Not Assessed

Additional Norwegian requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Electricity mix	Data source	Amount	Unit
Energy, electricity, Poland: 1 kWh	ecoinvent 3.6	1099,70	g CO2-ekv/kWh

Dangerous substances

The product contains no substances on the REACH Candidate list or the Norwegian priority list at or above 100 ppm, 0,01 % by weight.

Indoor environment

Additional environmental information

Key environmental indicators for options for this EPD: Cradle to Gate analyse from A1 to A3

Option number	Global warming (kg CO2)	Total energy use (MJ)	Share of recycled material in product(%)
Social® Turn - One chair in single box	33,95	496,49	51,53

Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.

ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.

EN 15804:2012+A1:2013 Environmental product declaration - Core rules for the product category of construction products.

ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.

ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.

lversen et al., (2018) eEPD v3.0 - Background information for EPD generator system. LCA.no report number 04.18

Vold et al., (2019) EPD generator for Norsk Industri, Background information for industry application and LCA data, LCA.no report number 06.19.

NPCR Part A: Construction products and services. Ver. 1.0. April 2017, EPD-Norge.

NPCR 026 Part B for Furniture. Ver. 2.0 October 2018, EPD-Norge.

C epd-norway Global Program Operator	Program operator and publisher The Norwegian EPD Foundation Post Box 5250 Majorstuen, 0303 Oslo,Norway	Phone: e-mail: web:	+47 23 08 80 00 post@epd-norge.no www.epd-norge.no
Varier.	Owner of the declaration	Phone:	+47 70 24 43 50
	Varier Furniture AS	e-mail:	info@varierfurniture.com
	Drammensveien 130 0277 Oslo	web:	www.varierfurniture.com
LCA	Author of the Life Cycle Assessment	Phone:	+47 916 50 916
	LCA.no AS	e-mail:	post@lca.no
	Dokka 6B 1671 Kråkerøy	web:	www.lca.no
LCA	Developer of EPD generator	Phone:	+47 916 50 916
	LCA.no AS	e-mail:	post@lca.no
	Dokka 1C 1671 Kråkerøy	web:	www.lca.no