

# Environmental product declaration

in accordance with ISO 14025 and EN 15804+A2

## Scotte RS (Beckers)







Beckers

**Owner of the declaration:** Tikkurila Oyj

Product: Scotte RS (Beckers)

**Declared unit:** 1 kg

**This declaration is based on Product Category Rules:** CEN Standard EN 15804:2012+A2:2019 serves as core PCR NPCR 009:2018 Part B for Technical - Chemical products in the building and construction industry **Program operator:** The Norwegian EPD Foundation

Declaration number:

NEPD-5427-4728-EN

**Registration number:** 

NEPD-5427-4728-EN

Issue date: 05.12.2023

Valid to: 05.12.2028

EPD Software: LCA.no EPD generator ID: 68067

The Norwegian EPD Foundation



## **General information**

**Product** Scotte RS (Beckers)

#### Program operator:

Post Box 5250 Majorstuen, 0303 Oslo, Norway The Norwegian EPD Foundation Phone: +47 23 08 80 00 web: post@epd-norge.no

Declaration number: NEPD-5427-4728-EN

#### This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012 + A2:2019 serves as core PCR NPCR 009:2018 Part B for Technical - Chemical products in the building and construction industry

#### Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

#### **Declared unit:**

1 kg Scotte RS (Beckers)

**Declared unit with option:** A1-A3,A4

Functional unit:

#### General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPD-Norway's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD-Norway, and iii) the process is reviewed annually by an independent third party verifier. See Appendix G of EPD-Norway's General Programme Instructions for further information on EPD tools

#### Verification of EPD tool:

Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPDNorway's procedures and guidelines for verification and approval of EPD tools.

Third party verifier:

Anne Rønning, Norsus AS

(no signature required)

#### **Owner of the declaration:**

Tikkurila Oyj Contact person: Tikkurila EPD-team Phone: +358 20 191 2000 e-mail: epd-team@tikkurila.com

Manufacturer:

Tikkurila Sverige AB / Beckers Färg

120 86 Stockholm, Sweden

#### Place of production:

Tikkurila Oyj Heidehofintie 2 01300 Vantaa, Finland

#### Management system:

ISO9001, 14001, 45001

## Organisation no:

FI01970674

Issue date: 05.12.2023

Valid to: 05.12.2028

#### Year of study:

2020

#### Comparability:

EPD of construction products may not be comparable if they not comply with EN 15804 and seen in a building context.

#### Development and verification of EPD:

The declaration is created using EPD tool lca.tools ver EPD2022.03, developed by LCA.no. The EPD tool is integrated in the company's management system, and has been approved by EPD Norway.

Developer of EPD: Elisabet Sahlin

Reviewer of company-specific input data and EPD: Dawid Góral

Approved:

Håkon Hauan Managing Director of EPD-Norway



## Product

#### **Product description:**

Scotte RS is a Roll- and sprayable lightfiller for joint- and, spredfilling. The filler can be used in dry indoor environments on substrates such as, concrete light concrete, mansonary, gypsum boards etc. The product can be used both for roller and spray application, is easy to work with and good filling properties.

#### **Product specification**

Packaging: 14-litre plastic bag and 14-litre plastic bucket.

All calculations of the packaging material is made with the 10 liters bucket that represent the majority of the market.

Materials	Value	Unit
Styrene acrylic copolymer	2,5-10	%
1,2-benzisothiazol-3(2H)-one (BIT)	<1, Ref SDS	%
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	<1, Ref SDS	%
Water	25-50	%
Light-weight filler	2,5-10	%
Dolomite	25-50	%

#### **Technical data:**

Binding agent: Latex co-polymer Solvent: Water pH: Approx. 9 Colour: Grey

#### Market:

Europe

#### **Reference service life, product**

Fillers have a limited shelf life and are date-marked. Unopened packaging can be kept in a dark place, free from frost, for up to 12 months. Containers that have been opened must be resealed well.

#### Reference service life, building

The EPD does not cover the service life of the building.

#### **LCA: Calculation rules**

#### **Declared unit:**

1 kg Scotte RS (Beckers)

#### Cut-off criteria:

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

#### **Allocation:**

The allocation is made in accordance with the provisions of EN 15804. Incoming energy and water and waste production in-house is allocated equally among all products through mass allocation. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

#### Data quality:

Specific data for the product composition are provided by the manufacturer. The data represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on EPDs according to EN 15804 and different LCA databases. The data quality of the raw materials in A1 is presented in the table below.

Materials	Source	Data quality	Year
Wet ready-mixed filler	Supplier	Project EPD	2020




## System boundaries (X=included, MND=module not declared, MNR=module not relevant)

	Pr	oduct stag	ge		ruction ion stage				Use stage					End of I	life stage		Beyond the system boundaries
Raw	materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De- construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery - Recycling-potential
A1		A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Х		Х	Х	Х	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND

#### System boundary:

A1-A4



### Additional technical information:

Meets CE-marking requirements in accordance with EN 13963. Manufactured in accordance with ISO 9001 and ISO 14001. When treating plasterboards, follow recommendations in accordance with EN 13963. Nordic Ecolabel. Basta.



## LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

This EPD covers the following modules: A1 (Raw material supply), A2 (Transport) and A3 (Manufacturing), A4 (Transport).

Transport from production place to user (A4)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, over 32 tonnes, EURO 5	53,3 %	300	0,023	l/tkm	6,90



## LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

Environmental	impact			
	Indicator	Unit	A1-A3	A4
(j)	GWP-total	kg CO <sub>2</sub> -eq	2,14E-01	2,73E-02
P	GWP-fossil	kg CO <sub>2</sub> -eq	2,65E-01	2,73E-02
P	GWP-biogenic	kg CO <sub>2</sub> -eq	-5,15E-02	1,12E-05
P	GWP-luluc	kg CO <sub>2</sub> -eq	2,16E-04	7,96E-06
Ò	ODP	kg CFC11 -eq	2,35E-08	6,30E-09
Car -	АР	mol H+ -eq	2,16E-03	1,15E-04
<del></del>	EP-FreshWater	kg P -eq	1,09E-05	2,08E-07
<del></del>	EP-Marine	kg N -eq	3,15E-04	3,45E-05
	EP-Terrestial	mol N -eq	3,19E-03	3,81E-04
	РОСР	kg NMVOC -eq	1,03E-03	1,23E-04
B	ADP-minerals&metals <sup>1</sup>	kg Sb -eq	4,15E-06	4,66E-07
B	ADP-fossil <sup>1</sup>	MJ	5,79E+00	4,24E-01
%	WDP <sup>1</sup>	m <sup>3</sup>	1,81E+01	3,25E-01

GWP-total = Global Warming Potential total; GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment: EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

"Reading example: 9,0 E-03 = 9,0\*10-3 = 0,009" \*INA Indicator Not Assessed

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

#### **Remarks to environmental impacts**

Scotte RS is labeled with the Nordic Ecolabel, license no 3097 0002.



Additional environm	Additional environmental impact indicators					
	Indicator	Unit	A1-A3	A4		
	PM	Disease incidence	1,43E-08	2,40E-09		
(ron) 2	IRP <sup>2</sup>	kgBq U235 -eq	1,55E-02	1,85E-03		
-	ETP-fw <sup>1</sup>	CTUe	5,33E+00	3,10E-01		
<u>م</u> هم ***	HTP-c <sup>1</sup>	CTUh	3,25E-10	0,00E+00		
<u>م</u> م ع	HTP-nc <sup>1</sup>	CTUh	3,83E-09	3,00E-10		
æ	SQP <sup>1</sup>	dimensionless	5,01E+00	4,86E-01		

PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Potential Soil Quality Index (dimensionless)

"Reading example: 9,0 E-03 = 9,0\*10-3 = 0,009" \*INA Indicator Not Assessed

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

2. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.



Resource use				
	Indicator	Unit	A1-A3	A4
	PERE	MJ	8,21E-01	5,34E-03
Z,	PERM	MJ	4,93E-01	0,00E+00
° <b>∓</b> 3	PERT	MJ	1,31E+00	5,34E-03
A	PENRE	MJ	4,85E+00	4,24E-01
.Åe	PENRM	MJ	1,24E+00	0,00E+00
IA la	PENRT	MJ	6,09E+00	4,24E-01
	SM	kg	9,90E-04	0,00E+00
	RSF	MJ	1,82E-02	1,87E-04
Ū.	NRSF	MJ	5,65E-03	6,26E-04
\$	FW	m <sup>3</sup>	5,05E-03	4,83E-05

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non-renewable primary energy resources; SENRE = Use of non renewable primary energy resources; SENRE = Use of secondary materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary materials; RERT = Total use of non renewable primary energy resources; SM = Use of secondary materials; RERT = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Net use of fresh water

"Reading example: 9,0 E-03 = 9,0\*10-3 = 0,009" \*INA Indicator Not Assessed



End of life - Waste				
	Indicator	Unit	A1-A3	A4
	HWD	kg	5,97E-03	2,32E-05
Ū	NHWD	kg	8,43E-02	3,69E-02
8	RWD	kg	1,57E-05	2,90E-06

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed

"Reading example: 9,0 E-03 = 9,0\*10-3 = 0,009" \*INA Indicator Not Assessed

End of life - Output flow				
Indicator		Unit	A1-A3	A4
¢⊳	CRU	kg	0,00E+00	0,00E+00
\$\$ <b>\</b>	MFR	kg	2,31E-03	0,00E+00
D₽	MER	kg	1,59E-04	0,00E+00
$\overline{\gamma}$	EEE	MJ	6,54E-03	0,00E+00
DQ	EET	MJ	9,89E-02	0,00E+00

CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported energy electrical; EET = Exported energy thermal

"Reading example: 9,0 E-03 = 9,0\*10-3 = 0,009" \*INA Indicator Not Assessed

Biogenic Carbon Content					
Indicator	Unit	At the factory gate			
Biogenic carbon content in product	kg C	0,00E+00			
Biogenic carbon content in accompanying packaging	kg C	1,47E-02			

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO2



## **Additional requirements**

#### Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

#### Dangerous substances

The product contains no substances given by the REACH Candidate list.

Indoor environment

## **Additional Environmental Information**

Additional environmental impact indicators required in NPCR Part A for construction products					
Indicator Unit A1-A3 A4					
GWPIOBC	kg CO <sub>2</sub> -eq	1,60E-01	2,73E-02		

GWP-IOBC: Global warming potential calculated according to the principle of instantaneous oxidation. In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.



## Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.

ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.

EN 15804:2012 + A2:2019 Environmental product declaration - Core rules for the product category of construction products.

ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.

ecoinvent v3, (2019) Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.

Iversen et al., (2021) eEPD v2021.09 Background information for EPD generator tool system verification, LCA.no Report number: 07.21

Iversen et al., (2020) EPD generator - Background information and LCA data for customer.

NPCR Part A: Construction products and services. Ver. 2.0, 24.03.2021 EPD Norway.

NPCR 009 Part B for technical-chemical products. Ver. 2.0 October 2021, EPD-Norge.

C epd-norway	Program operator and publisher	Phone: +47 23 08 80 00
	The Norwegian EPD Foundation	e-mail: post@epd-norge.no
Global Program Operator	Post Box 5250 Majorstuen, 0303 Oslo, Norway	web: www.epd-norge.no
	Owner of the declaration:	Phone: +358 20 191 2000
	Tikkurila Oyj	e-mail: epd-team@tikkurila.co
TIKKURILA	Heidehofintie 2, 01300 Vantaa	web: www.tikkurilagroup.con
$\bigcirc$	Author of the Life Cycle Assessment	Phone: +47 916 50 916
(LCA)	LCA.no AS	e-mail: post@lca.no
,no	Dokka 6B, 1671	web: www.lca.no
$\bigcirc$	Developer of EPD generator	Phone: +47 916 50 916
(LCA)	LCA.no AS	e-mail: post@lca.no
no	Dokka 6B,1671 Kråkerøy	web: www.lca.no
ECO PLATFORM	ECO Platform	web: www.eco-platform.org
	ECO Portal	web: ECO Portal