

Environmental product declaration

in accordance with ISO 14025 and EN 15804+A2

EFG One Sync. without armrest & neckrest, mesh back closed and excl. fabric on seat



The Norwegian EPD Foundation

Owner of the declaration:

EFG European Furniture Group AB

Product:

EFG One Sync. without armrest & neckrest, mesh back closed and excl. fabric on seat

Declared unit:

1 pcs

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR
NPCR 026:2022 Part B for Furniture

Program operator:

The Norwegian EPD Foundation

Declaration number:

NEPD-5541-4843-EN

Registration number:

NEPD-5541-4843-EN

Issue date: 08.12.2023

Valid to: 08.12.2028

EPD Software:

LCA.no EPD generator ID: 159896

General information

Product

EFG One Sync. without armrest & neckrest, mesh back closed and excl. fabric on seat

Program operator:

Post Box 5250 Majorstuen, 0303 Oslo, Norway
The Norwegian EPD Foundation
Phone: +47 23 08 80 00
web: post@epd-norge.no

Declaration number:

NEPD-5541-4843-EN

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR
NPCR 026:2022 Part B for Furniture

Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Declared unit:

1 pcs EFG One Sync. without armrest & neckrest, mesh back closed and excl. fabric on seat

Declared unit (cradle to gate) with option:

A1-A3,A4,A5,B2,B3,B4,C1,C2,C3,C4,D

Functional unit:

Office chair

General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPD-Norway's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD-Norway, and iii) the process is reviewed annually by an independent third party verifier. See Appendix G of EPD-Norway's General Programme Instructions for further information on EPD tools

Verification of EPD tool:

Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPDNorway's procedures and guidelines for verification and approval of EPD tools.

Third party verifier:

Elisabet Amat, GREENIZE projects

(no signature required)

Owner of the declaration:

EFG European Furniture Group AB
Contact person: Christer Johansson
Phone:
e-mail: christer.johansson@efg.se

Manufacturer:

EFG European Furniture Group AB

Place of production:

EFG European Furniture Group AB

, Norway

Management system:

ISO 14001

Organisation no:

Issue date: 08.12.2023

Valid to: 08.12.2028

Year of study:

2023

Comparability:

EPD of construction products may not be comparable if they not comply with EN 15804 and seen in a building context.

Development and verification of EPD:

The declaration is created using EPD tool lca.tools ver EPD2022.03, developed by LCA.no. The EPD tool is integrated in the company's management system, and has been approved by EPD Norway.

Developer of EPD: Andreas Mattisson

Reviewer of company-specific input data and EPD: Christer Johansson

Approved:



Håkon Hauan, CEO EPD-Norge

Product

Product description:

Task chair

Product specification

Task chair

Materials	kg	%	Recycled share in material (kg)	Recycled share in material (%)
Metal - Aluminium	2,09	19,37	2,09	100,00
Metal - Steel	2,61	24,16	0,00	0,00
Plastic - Nylon (PA)	5,06	46,86	0,00	0,00
Plastic - Polyurethane (PUR)	0,60	5,59	0,00	0,00
Polyester textile	0,44	4,03	0,01	2,02
Total	10,80		2,10	

Packaging	kg	%	Recycled share in material (kg)	Recycled share in material (%)
Packaging - Cardboard	1,06	96,73	0,38	36,00
Packaging - Plastic	0,04	3,27	0,00	0,00
Total incl. packaging	11,90		2,48	

Technical data:

Market:

Scandinavia

Reference service life, product

15 year

Reference service life, building

LCA: Calculation rules

Declared unit:

1 pcs EFG One Sync. without armrest & neckrest, mesh back closed and excl. fabric on seat

Cut-off criteria:

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

Allocation:

The allocation is made in accordance with the provisions of EN 15804. Incoming energy and water and waste production in-house is allocated equally among all products through mass allocation. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

Data quality:


Specific data for the product composition are provided by the manufacturer. They represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on registered EPDs according to EN 15804, Ostfold Research databases, ecoinvent and other LCA databases. The data quality of the raw materials in A1 is presented in the table below.

Materials	Source	Data quality	Year
Metal - Aluminium	ecoinvent 3.6	Database	2019
Metal - Steel	ecoinvent 3.6	Database	2019
Packaging - Cardboard	ecoinvent 3.6	Database	2019
Packaging - Plastic	ecoinvent 3.6	Database	2019
Plastic - Nylon (PA)	ecoinvent 3.6	Database	2019
Plastic - Polyurethane (PUR)	ecoinvent 3.6	Database	2019
Polyester textile	ecoinvent 3.6	Database	2019

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Product stage			Construction installation stage		Use stage						End of life stage				Beyond the system boundaries	
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	X	X	X	MND	MND	MND	X	X	X	X	X

System boundary:



Additional technical information:

LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

Check out www.efg.se for caring instructions

Transport from production place to user (A4)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, 16-32 tonnes, EURO 5 (km)	36,7 %	300	0,044	l/tkm	13,20
Assembly (A5)					
	Unit	Value			
Waste, packaging, corrugated board box, to average treatment (kg)	kg	1,06			
Waste, packaging, plastic film (LDPE), to average treatment - A5 (kg)	kg	0,04			
Maintenance (B2)					
	Unit	Value			
Household detergent, 5% soap solution (kg)	kg/DU	1,00			
Wastewater, average treatment (m3)	m3	0,00			
Transport to waste processing (C2)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, 16-32 tonnes, EURO 5 (km)	36,7 %	85	0,044	l/tkm	3,74
Waste processing (C3)					
	Unit	Value			
Waste treatment per kg Non-hazardous waste, incineration with fly ash extraction - C3 (kg)	kg	0,44			
Waste treatment per kg Plastics, Mixture, municipal incineration with fly ash extraction (kg)	kg	5,06			
Waste treatment per kg Polyurethane (PU), incineration (kg)	kg	0,60			
Waste treatment per kg Scrap aluminium, incineration with fly ash extraction (kg)	kg	2,09			
Waste treatment per kg Scrap steel, incineration with fly ash extraction (kg)	kg	2,61			
Waste, materials to recycling (kg)	kg	1,10			
Disposal (C4)					
	Unit	Value			
Landfilling of ashes and residues from incineration of Scrap aluminium (kg)	kg	1,87			
Landfilling of ashes and residues from incineration of Scrap steel (kg)	kg	1,72			
Landfilling of ashes from incineration of Non-hazardous waste, process per kg ashes and residues - C4 (kg)	kg	0,10			
Landfilling of ashes from incineration of Plastics, Mixture, municipal incineration with fly ash extraction, process per kg ashes and residues - C4 (kg)	kg	0,18			
Landfilling of ashes from incineration of Polyurethane (PU), process per kg ashes and residues - C4 (kg)	kg	0,02			
Benefits and loads beyond the system boundaries (D)					
	Unit	Value			
Substitution of electricity, in Norway (MJ)	MJ	8,88			
Substitution of primary steel with net scrap (kg)	kg	0,89			
Substitution of thermal energy, district heating, in Norway (MJ)	MJ	134,39			

LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

Environmental impact							
Indicator	Unit	A1-A3	A4	A5	B2	B3	
GWP-total	kg CO ₂ -eq	7,47E+01	5,96E-01	1,83E+00	3,19E-01	0	
GWP-fossil	kg CO ₂ -eq	7,62E+01	5,95E-01	2,01E-02	1,11E-01	0	
GWP-biogenic	kg CO ₂ -eq	-1,63E+00	2,43E-04	1,81E+00	5,16E-02	0	
GWP-luluc	kg CO ₂ -eq	9,43E-02	2,08E-04	5,91E-06	1,56E-01	0	
ODP	kg CFC11 -eq	2,35E-06	1,36E-07	3,81E-09	1,86E-08	0	
AP	mol H ⁺ -eq	3,10E-01	2,43E-03	8,50E-05	1,31E-03	0	
EP-FreshWater	kg P -eq	2,19E-03	4,67E-06	1,47E-07	7,99E-04	0	
EP-Marine	kg N -eq	6,74E-02	7,21E-04	3,02E-05	1,34E-03	0	
EP-Terrestrial	mol N -eq	6,82E-01	7,98E-03	3,04E-04	4,40E-03	0	
POCP	kg NMVOC -eq	2,36E-01	2,44E-03	8,80E-05	7,47E-04	0	
ADP-minerals&metals ¹	kg Sb -eq	9,41E-03	1,61E-05	4,34E-07	6,77E-06	0	
ADP-fossil ¹	MJ	9,86E+02	8,97E+00	2,53E-01	1,21E+00	0	
WDP ¹	m ³	5,06E+03	8,56E+00	3,47E-01	2,57E+00	0	

Indicator	Unit	B4	C1	C2	C3	C4	D
GWP-total	kg CO ₂ -eq	0	0	1,69E-01	1,47E+01	4,13E-02	-1,78E+00
GWP-fossil	kg CO ₂ -eq	0	0	1,69E-01	1,47E+01	4,13E-02	-1,75E+00
GWP-biogenic	kg CO ₂ -eq	0	0	6,87E-05	7,39E-04	3,06E-05	-2,15E-03
GWP-luluc	kg CO ₂ -eq	0	0	5,89E-05	8,13E-05	1,24E-05	-2,73E-02
ODP	kg CFC11 -eq	0	0	3,84E-08	4,34E-08	1,26E-08	-5,68E-02
AP	mol H ⁺ -eq	0	0	6,89E-04	4,47E-03	2,89E-04	-1,13E-02
EP-FreshWater	kg P -eq	0	0	1,32E-06	4,15E-06	4,15E-07	-1,29E-04
EP-Marine	kg N -eq	0	0	2,04E-04	2,23E-03	1,03E-04	-3,10E-03
EP-Terrestrial	mol N -eq	0	0	2,26E-03	2,23E-02	1,14E-03	-3,29E-02
POCP	kg NMVOC -eq	0	0	6,92E-04	5,39E-03	3,28E-04	-1,11E-02
ADP-minerals&metals ¹	kg Sb -eq	0	0	4,57E-06	2,02E-06	7,05E-07	-2,46E-05
ADP-fossil ¹	MJ	0	0	2,54E+00	2,74E+00	9,35E-01	-1,93E+01
WDP ¹	m ³	0	0	2,43E+00	1,18E+01	1,90E+00	-8,82E+01

GWP-total = Global Warming Potential total; GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

"Reading example: 9,0 E-03 = 9,0*10⁻³ = 0,009"

*INA Indicator Not Assessed

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

Remarks to environmental impacts

Additional environmental impact indicators

Indicator	Unit	A1-A3	A4	A5	B2	B3
PM	Disease incidence	3,28E-06	4,28E-08	1,27E-09	1,85E-08	0
IRP ²	kgBq U235 -eq	2,49E+00	3,92E-02	1,08E-03	4,37E-03	0
ETP-fw ¹	CTUe	9,15E+02	6,61E+00	3,32E-01	1,03E+01	0
HTP-c ¹	CTUh	8,27E-08	0,00E+00	1,00E-11	2,60E-10	0
HTP-nc ¹	CTUh	6,57E-07	7,14E-09	4,14E-10	6,02E-09	0
SQP ¹	dimensionless	1,89E+02	6,19E+00	1,82E-01	6,31E+00	0

Indicator	Unit	B4	C1	C2	C3	C4	D
PM	Disease incidence	0	0	1,21E-08	2,46E-08	5,28E-09	-4,70E-07
IRP ²	kgBq U235 -eq	0	0	1,11E-02	6,47E-03	3,76E-03	-6,77E-02
ETP-fw ¹	CTUe	0	0	1,87E+00	4,37E+01	5,63E-01	-1,15E+02
HTP-c ¹	CTUh	0	0	0,00E+00	1,04E-09	2,00E-11	-5,80E-09
HTP-nc ¹	CTUh	0	0	2,02E-09	3,92E-08	5,55E-10	4,37E-08
SQP ¹	dimensionless	0	0	1,75E+00	4,63E-01	2,03E+00	-7,51E+01

PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Soil Quality (dimensionless)

"Reading example: 9,0 E-03 = 9,0*10⁻³ = 0,009"

*INA Indicator Not Assessed

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator
2. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Resource use								
Indicator		Unit	A1-A3	A4	A5	B2	B3	
	PERE	MJ	5,52E+01	1,27E-01	4,26E-03	1,69E+00	0	
	PERM	MJ	8,72E+00	0,00E+00	-8,72E+00	0,00E+00	0	
	PERT	MJ	6,40E+01	1,27E-01	-8,72E+00	1,69E+00	0	
	PENRE	MJ	7,58E+02	8,97E+00	2,53E-01	1,43E+00	0	
	PENRM	MJ	2,27E+02	0,00E+00	-1,53E+00	0,00E+00	0	
	PENRT	MJ	9,86E+02	8,97E+00	-1,28E+00	1,43E+00	0	
	SM	kg	2,52E+00	0,00E+00	0,00E+00	0,00E+00	0	
	RSF	MJ	1,21E+00	4,53E-03	1,39E-04	1,80E-03	0	
	NRSF	MJ	2,60E-01	1,62E-02	5,62E-04	2,55E-03	0	
	FW	m ³	7,97E-01	9,45E-04	1,20E-04	1,63E-02	0	

Indicator		Unit	B4	C1	C2	C3	C4	D
	PERE	MJ	0	0	3,59E-02	1,38E-01	1,76E-02	-6,95E+01
	PERM	MJ	0	0	0,00E+00	0,00E+00	0,00E+00	0,00E+00
	PERT	MJ	0	0	3,59E-02	1,38E-01	1,76E-02	-6,95E+01
	PENRE	MJ	0	0	2,54E+00	2,79E+00	9,35E-01	-1,93E+01
	PENRM	MJ	0	0	0,00E+00	-2,26E+02	0,00E+00	0,00E+00
	PENRT	MJ	0	0	2,54E+00	-2,23E+02	9,35E-01	-1,93E+01
	SM	kg	0	0	0,00E+00	0,00E+00	0,00E+00	0,00E+00
	RSF	MJ	0	0	1,28E-03	3,04E-03	4,66E-04	2,31E-02
	NRSF	MJ	0	0	4,58E-03	0,00E+00	2,09E-02	-3,06E+00
	FW	m ³	0	0	2,68E-04	1,69E-02	8,43E-04	-8,49E-02

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary materials; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Net use of fresh water

"Reading example: 9,0 E-03 = 9,0*10⁻³ = 0,009"

*INA Indicator Not Assessed

End of life - Waste								
Indicator		Unit	A1-A3	A4	A5	B2	B3	
	HWD	kg	3,44E-01	4,58E-04	0,00E+00	1,61E-02	0	
	NHWD	kg	8,32E+00	4,29E-01	1,10E+00	4,64E-02	0	
	RWD	kg	1,81E-03	6,12E-05	0,00E+00	4,78E-06	0	

Indicator		Unit	B4	C1	C2	C3	C4	D
	HWD	kg	0	0	1,30E-04	0,00E+00	3,70E+00	-5,59E-03
	NHWD	kg	0	0	1,22E-01	4,35E-01	5,66E-02	-6,61E-01
	RWD	kg	0	0	1,73E-05	0,00E+00	5,88E-06	-5,56E-05

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed

*Reading example: 9,0 E-03 = $9,0 \cdot 10^{-3}$ = 0,009

*INA Indicator Not Assessed

End of life - Output flow								
Indicator		Unit	A1-A3	A4	A5	B2	B3	
	CRU	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0	
	MFR	kg	1,21E+00	0,00E+00	1,01E+00	0,00E+00	0	
	MER	kg	5,69E-04	0,00E+00	7,44E-02	0,00E+00	0	
	EEE	MJ	5,37E-02	0,00E+00	6,09E-02	0,00E+00	0	
	EET	MJ	8,13E-01	0,00E+00	9,21E-01	0,00E+00	0	

Indicator		Unit	B4	C1	C2	C3	C4	D
	CRU	kg	0	0	0,00E+00	0,00E+00	0,00E+00	0,00E+00
	MFR	kg	0	0	0,00E+00	1,10E+00	0,00E+00	0,00E+00
	MER	kg	0	0	0,00E+00	1,08E+01	0,00E+00	0,00E+00
	EEE	MJ	0	0	0,00E+00	8,77E+00	0,00E+00	0,00E+00
	EET	MJ	0	0	0,00E+00	1,33E+02	0,00E+00	0,00E+00

CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported energy electrical; EET = Exported energy thermal

*Reading example: 9,0 E-03 = $9,0 \cdot 10^{-3}$ = 0,009

*INA Indicator Not Assessed

Biogenic Carbon Content		
Indicator	Unit	At the factory gate
Biogenic carbon content in product	kg C	0,00E+00
Biogenic carbon content in accompanying packaging	kg C	4,93E-01

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO₂

Additional requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Electricity mix	Data source	Amount	Unit
Electricity, Sweden (kWh)	ecoinvent 3.6	54,94	g CO ₂ -eq/kWh

Dangerous substances

The product contains no substances given by the REACH Candidate list.

Indoor environment

Additional Environmental Information

Key Environmental Indicators

Key environmental indicators	Unit	A1-A3	A4	A1-C4	A1-D
GWPtotal	kg CO ₂ -eq	74,66	0,60	92,27	90,48
Total energy consumption	MJ	814,42	9,12	833,41	741,56
Amount of recycled materials	%	20,87			

Additional environmental impact indicators required in NPCR Part A for construction products

Indicator	Unit	A1-A3	A4	A5	B2	B3
GWPIOBC	kg CO ₂ -eq	7,64E+01	5,96E-01	0,00E+00	6,13E-01	0

Indicator	Unit	B4	C1	C2	C3	C4	D
GWPIOBC	kg CO ₂ -eq	0	0	1,69E-01	1,42E+01	5,68E-02	-2,25E+00

GWPI-IOBC: Global warming potential calculated according to the principle of instantaneous oxidation. In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.

Variants and Options

Key environmental indicators (A1-A3) for variants of this EPD

Variants	Weight (kg)	GWPtotal (kg CO ₂ -eq)	Total energy consumption (MJ)	Amount of recycled materials (%)
EFG One Sync. low back without armrest & neckrest, upholstered back and seat excl. fabric	10,37	46,73	613,26	33,97
EFG One Sync. without armrest & neckrest, upholstered back and seat excl. fabric	11,67	48,81	647,70	33,79

Key environmental indicators (A1-A3) for options for this EPD

Options	Weight (kg)	GWPtotal (kg CO ₂ -eq)	Total energy consumption (MJ)	Amount of recycled materials (%)
Efg One armrests	1,71	15,62	199,25	0,00
EFG One Neckrest Mesh	0,77	8,86	130,79	0,09
EFG One Neckrest upholstered excl. fabric	0,84	9,05	133,32	0,00

Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.
 ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.
 EN 15804:2012+A2:2019 Environmental product declaration - Core rules for the product category of construction products.
 ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.
 ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.
 Iversen et al., (2021) eEPD v2021.09 Background information for EPD generator tool system verification, LCA.no Report number: 07.21
 Ruud et al., (2023) EPD generator for NPCR026 Part B for Furniture - Background information for EPD generator application and LCA data, LCA.no report number 01.23
 NPCR Part A: Construction products and services. Ver. 2.0. March 2021, EPD-Norge.
 NPCR 026 Part B for Furniture. Ver. 2.0 March 2022, EPD-Norge.

<p>Global Program Operator</p>	<p>Program operator and publisher The Norwegian EPD Foundation Post Box 5250 Majorstuen, 0303 Oslo, Norway</p>	<p>Phone: +47 23 08 80 00 e-mail: post@epd-norge.no web: www.epd-norge.no</p>
	<p>Owner of the declaration: EFG European Furniture Group AB</p>	<p>Phone: e-mail: christer.johansson@efg.se web: https://www.efg.se</p>
	<p>Author of the Life Cycle Assessment LCA.no AS Dokka 6B, 1671</p>	<p>Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no</p>
	<p>Developer of EPD generator LCA.no AS Dokka 6B,1671 Kråkerøy</p>	<p>Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no</p>
	<p>ECO Platform ECO Portal</p>	<p>web: www.eco-platform.org web: ECO Portal</p>